

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	14APR2015	DW	CW
	B	ECR-15-018270	09DEC2015	DW	CW
	B1	ECR-16-006849	13MAY2016	RL	CW
	C	ECR-21-111798	28SEP2021	WQR	CW

T2111122201-000 SHOWN,  
带 LOGO, 产品型号, 认证标示



T2111122201-001 SHOWN, ALL DIMENSIONS ARE  
SAME AS T2111122201-000, EXCEPT WITHOUT LOGO,  
TYPE DESCRIPTION, TUV AND CUL MARK  
不带 LOGO, 产品型号和认证标示

NOTES:

- TECHNICAL CHARACTERISTICS:  
INSULATION MATERIAL: PC  
RATED VOLTAGE: 250V  
RATED CURRENT: 10A  
INSULATION RESISTANCE:  $\geq 400M\Omega$   
RATED IMPULSE VOLTAGE: 4KV  
POLLUTION DEGREE: 3  
FLAMMABILITY: UL94V-0  
MATING CYCLES: 500 CYCLES  
OPERATION TEMPERATURE:  $-40\sim+125^{\circ}C$   
WIRE RANGE:  $0.14\sim 2.5\text{ mm}^2$  (26~14 AWG)  
CONTACT TYPE: CRIMP CONTACT
- CONTACT NEED TO BE ORDERED SEPARATELY.  
(ORDER No. REFER TO DRAWING: T20200X20XX000)

注释:

- 技术参数:  
绝缘材料: PC  
额定电压: 250V  
额定电流: 10A  
绝缘电阻:  $\geq 400M\Omega$   
额定脉冲电压: 4KV  
污染等级: 3  
阻燃等级: UL94V-0  
插拔次数: 500次  
工作温度:  $-40\sim+125^{\circ}C$   
接线范围:  $0.14\sim 2.5\text{ mm}^2$  (26~14 AWG)  
接线类型: 冷压接
- 端子需要单独订购.  
(订货号参考图面: T20200X20XX000)

T2111122201-001	HMN-012-F WITHOUT LOGO HMN-012模块母插 不带LOGO, 产品型号和认证标示
T2111122201-000	HMN-012-F WITH LOGO HMN-012模块母插
PART NUMBER 料号	PART DESCRIPTION 描述

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:	TOLERANCES UNLESS OTHERWISE SPECIFIED:
mm	
	0 PLC $\pm$
	1 PLC $\pm$
	2 PLC $\pm$
	3 PLC $\pm$
	4 PLC $\pm$
	ANGLES $\pm$
MATERIAL	FINISH
-	-
-	-

DWN	14APR2015	David Wang
CHK	14APR2015	Chris Wang
APVD	14APR2015	Xiang Xu
PRODUCT SPEC	108-137121	
APPLICATION SPEC	114-137121	
WEIGHT	-	
Customer Drawing		

<b>TE</b> TE Connectivity			
NAME HMN-012-F			
SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	00779	©-T2111122201000	-
SCALE		SHEET	REV
1:1		1 OF 1	C

1470-19 (3/13)

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[T2111122201-000](#)