

| LOC |     | DIST                                                                                                                                                                                            |  | REVISIONS |     |      |  |
|-----|-----|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|-----------|-----|------|--|
| P   | LTR | DESCRIPTION                                                                                                                                                                                     |  | DATE      | DWN | APVD |  |
|     | G   | Contact pin base material change from CuSn (Phosphor bronze) to CuZn (Brass). Plating change from min. 0.8microns gold plating to min. 0.7µm Pd Ni + 0.1µm gold flash at contact area (Area F). |  | 24JUN2014 | TJ  | JK   |  |

| NUMBER        |  | 825440    |  |
|---------------|--|-----------|--|
| VERWENDET FÜR |  | E 92-9802 |  |
| WAR NR.       |  | —         |  |

| POLZ. PRO REIHE | L±0.5  | BESTELL-NR. |    |
|-----------------|--------|-------------|----|
| —               | —      | —           |    |
| 2               | 5.08   | 825 440     | -2 |
| 3               | 7.62   |             | -3 |
| 4               | 10.16  |             | -4 |
| 5               | 12.70  |             | -5 |
| 6               | 15.24  |             | -6 |
| 7               | 17.78  |             | -7 |
| 8               | 20.32  |             | -8 |
| 9               | 22.86  |             | -9 |
| 10              | 25.40  | 1-          | -0 |
| 11              | 27.94  | 1-          | -1 |
| 12              | 30.48  | 1-          | -2 |
| 13              | 33.02  | 1-          | -3 |
| 14              | 35.56  | 1-          | -4 |
| 15              | 38.10  | 1-          | -5 |
| 16              | 40.64  | 1-          | -6 |
| 17              | 43.18  | 1-          | -7 |
| 18              | 45.72  | 1-          | -8 |
| 19              | 48.26  | 1-          | -9 |
| 20              | 50.80  | 2-          | -0 |
| 21              | 53.34  | 2-          | -1 |
| 22              | 55.88  | 2-          | -2 |
| 23              | 58.42  | 2-          | -3 |
| 24              | 60.96  | 2-          | -4 |
| 25              | 63.50  | 2-          | -5 |
| 26              | 66.04  | 2-          | -6 |
| 27              | 68.58  | 2-          | -7 |
| 28              | 71.12  | 2-          | -8 |
| 29              | 73.66  | 2-          | -9 |
| 30              | 76.20  | 3-          | -0 |
| 31              | 78.74  | 3-          | -1 |
| 32              | 81.28  | 3-          | -2 |
| 33              | 83.82  | 3-          | -3 |
| 34              | 86.36  | 3-          | -4 |
| 35              | 88.90  | 3-          | -5 |
| 36              | 91.44  | 3-          | -6 |
| 37              | 93.98  | 3-          | -7 |
| 38              | 96.52  | 3-          | -8 |
| 39              | 99.06  | 3-          | -9 |
| 40              | 101.60 | 4-          | -0 |
| 41              | 104.14 | 4-          | -1 |
| 42              | 106.68 | 4-          | -2 |
| 43              | 109.22 | 4-          | -3 |
| 44              | 111.76 | 4-          | -4 |
| 45              | 114.30 | 4-          | -5 |
| 46              | 116.84 | 4-          | -6 |
| 47              | 119.38 | 4-          | -7 |
| 48              | 121.92 | 4-          | -8 |
| 49              | 124.46 | 4-          | -9 |
| 50              | 127.00 | 5- 825 440  | -0 |

CAD-ORIGINAL  
ZEICHNUNG NICHT ÄNDERN


STECKSEITE: IM BEREICH "F" MIN 0.7µmPdNi+0.1µm GOLD FLASH ÜBER 1.27 µm NICKEL.  
LÖTSEITE: MIN. 2.5 µm ZINN ÜBER 1.27 µm NICKEL

| KONTAKTSTIFT | Cu Zn     | ⚠                |
|--------------|-----------|------------------|
| STIFTGEHÄUSE | PBT GV    | GRÜN             |
| BENENNUNG    | WERKSTOFF | OBERFLÄCHE FARBE |

ZEICHNUNG GÜLTIG AB KW 39/96

| DIMENSIONS:                            |  | DWN              | 22.06.84  | MATERIAL         | FINISH    |            |               |     |   |
|----------------------------------------|--|------------------|-----------|------------------|-----------|------------|---------------|-----|---|
| mm                                     |  | M.SCHAARSCHMIDT  |           | —                | —         |            |               |     |   |
| TOLERANCES UNLESS OTHERWISE SPECIFIED: |  | CHK              | —         | TE Connectivity  |           |            |               |     |   |
| ±0.2 mm                                |  | APVD             | —         |                  |           |            |               |     |   |
| 0 PLC ± —                              |  | PRODUCT SPEC     | 108-18012 |                  |           |            |               |     |   |
| 1 PLC ± —                              |  | APPLICATION SPEC | —         |                  |           |            |               |     |   |
| 2 PLC ± —                              |  | WEIGHT           | —         | SIZE             | CAGE CODE | DRAWING NO | RESTRICTED TO |     |   |
| 3 PLC ± —                              |  |                  |           | A4               | 00779     | C-825440   | —             |     |   |
| 4 PLC ± —                              |  |                  |           | CUSTOMER DRAWING |           |            |               |     |   |
| ANGLES ± —                             |  |                  |           | SCALE            | 4:1       | SHEET      | 1 OF 2        | REV | G |



LOC  
—

DIST  
—

REVISIONS

P

LTR

DESCRIPTION

DATE

DWN

APVD

—

—

SEE SHEET 1

—

—

—

VERWENDET FÜR  
E 92-9802

WAR NR. —

CAD-ORIGINAL  
ZEICHNUNG NICHT ÄNDERN

| Polz.<br>pro<br>Reihe | L±0.5 | Bestell-Nr.   | Bemerkung |
|-----------------------|-------|---------------|-----------|
| 1                     | 2.54  | 5- -1         |           |
| 2                     | 5.08  | 5- -2         |           |
| 3                     | 7.62  | 5- -3         |           |
| 4                     | 10.16 | 5- -4         |           |
| 5                     | 12.70 | 5- -5         |           |
| 6                     | 15.24 | 5- -6         |           |
| 7                     | 17.78 | 5- -7         |           |
| 8                     | 20.32 | 5- -8         |           |
| 9                     | 22.86 | 5- -9         |           |
| 10                    | 25.40 | 6- 0          |           |
| 11                    | 27.94 | 6- -1         |           |
| 12                    | 30.48 | 6- -2         |           |
| 13                    | 33.02 | 6- -3         |           |
| 14                    | 35.56 | 6- -4         |           |
| 15                    | 38.10 | 6- -5         |           |
| 16                    | 40.64 | 6- -6         |           |
| 17                    | 43.18 | 6- 825 440 -7 | △         |
| 18                    | 45.72 | 6- -8         |           |
| 19                    | 48.26 | 6- -9         |           |
| 20                    | 50.80 | 7- 0          |           |

△ VERPACKUNG:25 STÜCK IN PLASTIK-DOSE  
PN 165 439-1 MIT PLASTIK-DECKEL  
PN 165 440-1

△ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

△ OBSOLETE

| BENENNUNG                     | WERKSTOFF | OBERFLÄCHE<br>FARBE |
|-------------------------------|-----------|---------------------|
| ZEICHNUNG GÜLTIG AB KW 39./96 |           |                     |

DIMENSIONS:  
mm

TOLERANCES UNLESS  
OTHERWISE SPECIFIED:

0 PLC ± -  
1 PLC ± -  
2 PLC ± -  
3 PLC ± -  
4 PLC ± -  
ANGLES ± -

DWN A.HO 07.06.84  
CHK M.SCHAARSCHMIDT 13.06.84  
APVD -  
PRODUCT SPEC -  
APPLICATION SPEC -  
WEIGHT -

MATERIAL -

FINISH -

TE Connectivity

NAME  
AMPMODU II STIFTLEISTE  
ZWEIREIHIG

SIZE A4  
CAGE CODE 00779  
DRAWING NO C-825440

RESTRICTED TO  
-

CUSTOMER DRAWING

SCALE 4:1

SHEET 2 OF 2

REV G

RELEASED FOR PUBLICATION

ALL RIGHTS RESERVED.

THIS DRAWING IS UNPUBLISHED.

By -  
COPYRIGHT -

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[825440-6](#)